

BANDING SYSTEMS

EN/ES Flyer Nr. A18

- Easy, efficient and compact standard machine
- Wide range of different arch sizes
- High machine safety and easy accessibility
- Height adjustable and powerful performance
- With digital control unit DCP 2000

US-2000 AD












The US-2000 AD is a mobile, compact and automatic machine. The wide range of arch sizes allows an optimal adjustment to your product. To increase efficiency for our customers, we also offer special arch sizes on request, beside the standard arch line (see reverse side). The standard and adjustable fixed length mode or soft tension, enable tight and also gentle banding for soft products. The height adjustability and legroom also enable working from a seated position.





Nicht Sestziehen

The photocell is height adjustable and used for automatic release of the banding process.



Wide range of different arch sizes available.

Standard arch sizes at a glance

Width x Height in inch 10.24 x 4.72 / 7.09 / 10.24 14.17 x 7.09 / 10.24 / 14.17 / 19.69 19.69 x 10.24 / 14.17 / 19.69 27.56 x 10.24 / 14.17 / 21.65 35.43 x 10.24 / 14.17 / 19.69 only 1,18 inch belt guide 51.18 x 29.53 only 1,18 inch belt guide 66.93 x 14.17 only 1,18 inch belt guide Additional arch sizes upon request Band widths: 0.79 / 1.18 / 1.97 inch standard

optional

0.59 / 1.57 / 2.36 inch



800.456.3929 | sales@newaypkg.com www.newaypkg.com